

AvediaStream e2110



Supports Standard Definition (SD) encoding

Variety of input options: Composite, S-Video and RGBS

MPEG-2 video encoding from devices such as DVD players, set-top boxes and digital cameras



Technical Specifications

Video Input

Single Channel
Composite, S-Video, RGBS
RCA, 1V p-p 75Ω
PAL, SECAM, NTSC auto-switching
Resolutions supported: 525i 60Hz and 625i 50Hz
4:3/ 16:9 aspect ratio
Wide Screen Signalling for automatic aspect ratio switching

MPEG-2 Encoding

Main Profile @ Main Level
D1 video resolution
1.5Mbps – 15Mbps
Constant or variable bit rate

Audio Input

Unbalanced stereo

Audio Encoding

MPEG-1, Layer 2
Encoding bit rate 48Kbps – 384Kbps
Audio sampling rate 48KHz

IR Output

Control of AV source device

Network Interface

802.3 10/100BaseT Ethernet

Channel Streaming

Single program MPEG transport stream
RTP or UDP
IP multicast or one unicast address destination
Video or audio only options
Channel announcement using SAP/SDP

Network Protocols

TCP, UDP, DHCP (client), IGMP

Management

SNMP, TFTP, HTTP
Web management interface
Serial admin port

Control User Interface

Automatic or manual multicast address selection
Configure channel name, number, group membership
Stream on boot

Chassis Options

AvediaStream c1101 providing 1 Encoder
AvediaStream c1103 providing up to 3 Encoders
AvediaStream c1110 providing up to 10 Encoders

Power Consumption

10W Typical (15W Max)

e2110
Blade

Chassis

C1

C3

C10

Resolution

SD

More Information on MPEG Encoders

Encoder family product brochure
Encoder e2220, e2250, e3520, e3530 and e3550 Technical Specifications Datasheets
Chassis c1101, c1103 and c1110 Technical Specifications Datasheets

Head Office: Ridge Way, Hillend Industrial Park, Dalgety Bay, Dunfermline, UK, KY11 9JD

t: +44(0) 1383 828 250 f: +44(0) 1383 824 905 w: www.exterity.co.uk e: info@exterity.co.uk

© 2009 Exterity Ltd. All rights reserved. The Exterity Building IPTV logo, AvediaStream, AvediaServer, AvediaCentre and isocket are trademarks or registered trademarks of Exterity Ltd. The information and specification are subject to change without prior notice. Exterity tries to ensure that all information in this document is correct but does not accept liability for any error or omission.



Version

1.1

2009_10_06