

PRESENTATION RECORDER™ HD BASIC

Mobile: PR-HD-BASIC-M

Podium: PR-HD-BASIC-P



PRESENTATION RECORDING AND STREAMING

The PR-HD-BASIC-M/P captures video, audio and computer feeds together into a combined HD video that records the entire presentation to the very popular H.264/MP4 open standard. The PR-HD-BASIC-M/P may also simultaneously stream the resulting file either locally within a network or across the internet with the NCast Presentation Server or other content delivery services.

The PR-HD-BASIC-M/P fully automates this recording and streaming by offering a dedicated hardware solution with a powerful set of features.

The PR-HD-BASIC-M/P allows users to:

- Capture—several multimedia feeds: graphics, video, and audio,
- Compose—these feeds with PiP into a single multimedia stream,
- Encode—the stream into a standard MP4 (H.264) file,
- Cast—that file on the Internet using realtime streaming protocols,
- Archive—the stream for on-demand viewing.

The PR-HD-BASIC-M/P introduces support for up to WUXGA (1920x1200) input resolutions with up to WXGA (1280x720) capture resolutions and PiP (Picture-In-Picture) video and graphics overlay. The unit is a dedicated hardware solution that combines simple operation with a powerful set of features. Enjoy universal interoperability with any RGB/DVI source: laptops, PCs, MACs, document cameras, diagnostic equipment, etc.

The unit is easy to operate, simply plug in RGB (laptop, document camera, etc), DVI, video, and audio sources. Start and stop sessions using the web interface, serial commands or the ubiquitous Google calendar. The input signals will be automatically detected by the system and combined dynamically in a PiP (Picture-in-Picture) format. At the start of a session, this combined signal will be encoded as an MP4 file, and will then be available for streaming, recording and collaborating.

APPLICATIONS

- Presentation and Lecture Capture
- Corporate and Medical Training
- Simulations
- Events, Seminars, Conferences
- Focus Groups
- Interview Recordings
- Government Meetings



FEATURED HIGHLIGHTS

INTEGRATED VIDEO AND GRAPHICS

PR-HD technology integrates high resolution graphics and video sources into a PiP (Picture-in-Picture) or Picture-by-Picture format for H.264 playback.

PIP CUSTOMIZATION

Robust control set available for Picture-in-Picture technology, logo insertion and textual description. Graphical and dynamic text overlays add details.

CHANNEL/SESSION TEMPLATES

User-defined preset templates simplify session setup.

SCHEDULING

Schedule one or more Recorders using Google Calendar or other iCalendar based tools.

ROBUST

Embedded Linux kernel for secure, crash-free operation. Diskless operation for ultra-reliability. Green design, very low power.

SCALABLE

NCast technology allows for maximum scalability with remote users if streamed through multicast.

GRAPHICS RESOLUTION

Supports up to WUXGA (1920x1200) input and WXGA (1280x720) capture and streaming capabilities.

GRAPHICS QUALITY

Retain full integrity of original image using motion adaptive de-interlacing.

AUDIO CAPABILITIES

Audio input is fully synchronized with the video and graphics presentation for flawless playback.

RECORD CAPABILITIES

Archiving feature captures any source for later download or remote viewing.

PLAYBACK OPTIONS

Recorded archives auto-upload to a VOD server. H.264 encoding is compatible with Flash Media players.

COMPLETELY AUTOMATED

Automated scheduling, recording, work-flow processing, and distributing.

DESKTOP PLAYERS

Anyone connected to the network may view a presentation via a web browser or media player (Flash, Quicktime, VLC, HTML5 etc.) Playback by Windows Media Player and more.

TECHNICAL SPECIFICATIONS



Mobile: PR-HD-BASIC-M
Podium: PR-HD-BASIC-P

GRAPHIC AND VIDEO INPUTS

DVI-I (Laptops, HD Video)
RGB (DB15), Y-Pr-Pb
HDMI
Display Port
Composite Video
Supports: WUXGA, WXGA, XGA, SVGA, 720p, and 1080p

GRAPHICS RESOLUTIONS & PERFORMANCE

Simultaneously records and streams up to 720p (1280x720) at 30 fps

GRAPHICS OUTPUTS

WXGA (1280x720)
Y-Pb-Pr or RGB (DB15) 16.7 M colors, wide-screen displays
VGA loopback output connector

GRAPHICAL OVERLAYS

Add JPEG, PNG, and GIF images to the final screen composition
Dynamic text overlays add real-time titles and text

GRAPHICS COMPRESSION

H.264 (ISO/IEC 14496-10)

AUDIO

MP4, AAC (ISO 14496-3), Low Complexity Profile
Input Sampling, 16 Bits, 44.1 kHz
Input, Stereo, Line-In & Mic-In on 3.5mm Jack (PC Audio type)
Output, Stereo, Line Out, 3.5mm Jack (PC Audio type)
XLR Audio Level-Line Input Support, Mono only

NETWORK INTERFACE

RJ-45 (LAN, DSL, Cable Modem), Ethernet 10/100 Mbps, DHCP

COMMUNICATION PROTOCOLS

Multicast, Unicast, HTTP, HTTPS, UDP, TCP/IP, RTP, RTCP, RTSP, RTMP,
DHCP, NTP, FTP, SFTP, Telnet, SMTP, SNMP

EXTERNAL INTERFACES

Serial RS-232 port on DB-9 connector, USB, Power Connector

ENCODING BITRATES

Graphics 128 Kbps to 5 Mbps
Audio 16 Kbps to 128 Kbps

ENTERPRISE SYSTEM MANAGEMENT

Serial Crestron/AMX compatibility (Serial, Telnet, HTTP)
iCalendar support (Google Calendar)
Optional Java or Python Systems Manager
NCast Management Dashboard

PR-HD-BASIC SERIES MODELS

PR-HD-BASIC-M Mobile Recorder
PR-HD-BASIC-P Podium Recorder (Flange mount, any orientation)

ARCHIVE FEATURES – SOLID STATE DISK

Archive and record options – 32/64 GB storage
Archives stored as MP4 files or H.264 files (ISO 14496-14)
Playback using Windows Media Player, Quicktime, VLC, etc
Audio using MP4 AAC (ISO 14496-3)
Metadata index files with title, author, and subject
Saves to USB
Automated FTP and SSH FTP file push
Upload to NCast Presentation Server or Kaltura
Closed Caption SRT files

SETUP

USB Stick for IP Settings

USER INTERFACE CONTROLS

Capture size, Resolution and Aspect ratio
Graphics overlay positioning (vertical, horizontal)
PiP size, location (Overlap or Side-by-side)
Brightness, contrast, sharpness, saturation, hue
Audio Input Gain, Audio Output Volume
Dynamic text overlays, Closed Caption controls and Chapters
User-defined channel preset templates

STREAMING CAPABILITIES

Multicast, RTSP or RTMP Unicast to a Streaming Server
Flash Player, Quicktime, HTML5, DivX, VLC, and others supported

SECURITY

Embedded Linux OS, HTTPS, SSL Certificate, SSH FTP

DIMENSIONS AND WEIGHT

Mobile: 7.3" W (186.0mm) x 10.2" L (259.0mm)
x 2.3" H (58.5mm), 4 lbs (1.8 kg)
Podium: 8.25" W (209.6mm) x 10.25" L (260.3mm)
x 2.5" H (63.5mm), 3 lbs (1.4 kg)

POWER – GREEN DESIGN

Power Consumption: 30 Watts, 12V DC In
Power Supply: External AC Adapter 100-240V 50/60 Hz—60W

ENVIRONMENTAL OPERATION

Operating Temperature: 10° to 35°C (50° to 95°F)
Non-operating Temperature: -40° to 70°C (-40° to 158°F)
Operating Relative Humidity: 8% to 90% (non-condensing)
Non-operating Relative Humidity: 5 to 95% (non-condensing)

REGULATORY

FCC Part-15 Class A
EMC Directive 2004/108/EC
EMD Low Voltage Directive 2006/95/EC
RoHS Compliant 2002/95/EC

