

# Live transcoder

GPU-powered software for professional video encoding and transcoding.

Comprimato Live Transcoder is high-performance encoder and transcoder software built explicitly for live streaming.

It is designed for broadcasters and content distributors to match the low latency and high-quality requirements.

Live transcoder enables end-to-end live video production from contribution encoding up to final distribution transcoding.

It is available as a flexible software license and high-density server appliance. Live transcoder has been developed to help maximize revenue from content distribution by providing high-quality, cost-effective video processing.



## CONTRIBUTION ENCODING

Encode live video using H.264 or JPEG2000 TR-01 codecs and transport the video to the studio or directly to the cloud. Avoid packet loss, reduce latency, and deliver high-quality video.



## DISTRIBUTION TRANSCODING


Produce a high-quality video for live IPTV and OTT distribution. Create adaptive bitrate channels from IP inputs or directly from SDI sources.



## SOFTWARE-BASED SOLUTION

Comprimato Live Transcoder is GPU accelerated high-density software. It is available as a software license or 1RU server appliance.

End-to-end live video encoding and transcoding software.



# Additional features

---

## High Value Transcoding

---



### ABR transcoding

Instantly adapt live video content to the resolution, quality and codec needs of current and future devices.



### Image processing

Resizing, Change of sampling factor, Bit depth conversion, Interlacing/Deinterlacing, Framerate reduction, Color adjustments and others.



### High bitrate formats

Native support for high bitrate broadcasting contribution formats including JPEG2000, H.264 or HEVC.



### Low latency

End-to-end live video delivery with guaranteed latency cap of 700 ms.

## Lowest CapEx and OpEx

---



### Easy deployment

Software only solution simplifies deployment; no need for specialized support; maximum flexibility and portability.



### Investment protection

Fully leverages existing IT and IP infrastructure.



### Simple scalability

Extend the number of streams, resolution or frame rate simply by adding additional CPUs or GPUs.

## Easy integration and management

---



### 3<sup>rd</sup> party integration

Easy insertion into existing workflows via REST API.



### Centralized control

Set up, manage and control hundreds of streams from a single console via SNMP or web interface.

For more information contact [sales@comprimato.com](mailto:sales@comprimato.com)

| Feature on product roadmap

## Video input

### Supported codecs:

JPEG 2000  
H.264 (MPEG-4, AVC)  
H.265 (HEVC)  
MPEG-2

### SDI interface:

SD, HD, 3G-SDI

| Quad split 4K, 2SI 4K SDI

| 12G-SDI

### Resolutions:

FullHD 1080p  
4K UHD

### Color component sampling:

4:2:2 10bit/8bit  
4:2:0 10bit/8bit

## Audio input

### Codec:

Uncompressed PCM - multichannel  
(SMPTE 302M-2007)  
AAC  
MPEG2 Audio

AC-3

SDI audio (AES 3, Embedded AC3 - SMPTE 337)

| E-AC-3

## Metadata

SCTE-35, SCTE-104 + conversion

Metadata pass through

Subtitles embedding into H.264 SEI messages

Closed Captions (EIA-608/708)

Line 21 captions

## Video processing

- Resizing
  - Automatic color component subsampling (both configured automatically based on input and output settings)
  - De-Interlacing
  - Cropping / Padding
  - Color adjustments
  - Frame-rate adjustment (to 1/2)
- | • Logo insertion

## Containers & Protocols

UDP, RTP

MPEG-2 TS, MPTS

VSF TR-01

RTMP

SRT

| Transport stream File

## Synchronization

### Input PCR:

Configurable: global

(in separate transport stream) or local

(contained in each input transport stream)

### Output PTS:

Configurable: pass-through or adding offset

to input PTS

## Video output

Multiple output streams per each input stream, different configuration per each output stream.

### Video codec:

H.264 (MPEG4, AVC)

JPEG2000

H.265 (HEVC)

MPEG2

### SDI interface:

| SD, HD, 3G-SDI

| Quad split 4K, 2SI 4K SDI

| 12G-SDI

### Color component sampling:

4:2:2 10bit/8bit

4:2:0 10bit/8bit

## Audio output

### Audio codec:

AAC - multichannel

AC-3

Uncompressed PCM (SMPTE 302M-2007)

MPEG2 Audio

| E-AC-3

## Audio processing

- Shuffling
- Volume gain
- Sampling rate conversion

## System

### Input stream count:

Depends on HW configuration

### Output stream count:

Depends on HW configuration

### Latency (input to output):

Configurable, 700 down to 400 ms

### System type:

CentOS/RHEL OS custom image.

### Stream startup time:

Max. 5 seconds after configuration is applied

### Configuration options:

Web UI, SNMP, REST API

### System Monitoring options:

System webconsole, SNMP + custom OIDs